



REC 02

INDUSTRIA
INDUSTRY

RECASENS
BCN n 1886

Technical Textiles
PVC collection

RECASENS
BCN n 1886

We're woven differently

OFICINA CENTRAL / HEADQUARTERS:

Travessera de Gràcia, 18-20
08021 Barcelona (Spain)
Tel./Phone (+34) 93 200 27 00 · Fax (+34) 93 202 19 32
cial@recasens.com
export@recasens.com
www.recasens.com

@recasensfabrics





APLICACIONES / APPLICATIONS



CARACTERÍSTICAS DEL TEJIDO / FABRIC CHARACTERISTICS NORMA / NORM

Composición / Composition	Poliéster AT 1100 dtex recubierto de PVC / High Tenacity 1.100 dtex Polyester with PVC coating		
Tipo de tejido / Type of textile	Impermeable translúcido / Translucent waterproof finished		
Acabado / Finish	Mate / Matte		
Uso / Use	Exterior / Outdoor		

CARACTERÍSTICAS TÉCNICAS / TECHNICAL FEATURES

Peso / Weight	900 g/m ²	1100 g/m ²	1300 g/m ²	1400 g/m ²	UNE-EN ISO 2286-2
Espesor / Thickness	0,76 mm	1,00 mm	1,10 mm	1,15 mm	UNE-EN ISO 2286-3
Ancho / Width	300 cm				
Longitud de pieza / Standard Roll Length	30 / 150 m				
Resistencia a la Tracción (Urdimbre / Trama) / Tensile Strength (Warp / Weft)	400/350 daN/5 cm				UNE-EN ISO 13934-1
Resistencia al Desgarro (Urdimbre / Trama) / Tear Strength (Warp / Weft)	90/50 daN				UNE-EN ISO 4674-1
Adherencia del recubrimiento / Coating adhesion	10 daN/5 cm				Método interno basado en / Internal Method based on UNE-EN ISO 2411
Resistencia al frío y al calor / Heat and cold resistance	-30 °C / +70 °C				
Solidez del color a la luz artificial - Xenotest / Colour fastness to artificial light - Xenotest	7-8				UNE-EN ISO 105 B02
Solidez del color a la intemperie artificial - Xenotest / Colour fastness to artificial weathering - Xenotest	4-5				UNE-EN ISO 105 B04
Actividad antibacteriana / Antibacterial activity	Pasa / Pass				UNE-EN ISO 20645-05
Compatibilidad con contacto alimentario / Food contact compatibility	Pasa / Pass				Certificación IANESCO / IANESCO certification

Las características técnicas indicadas son valores medios con una tolerancia de +/- 5%.

Dado que nuestros productos están en constante evolución, en base a la demanda del mercado y a los avances técnicos, S.A. Recasens se reserva el derecho a modificar estos datos en todo momento, siendo responsabilidad del cliente verificar que los datos que está consultando corresponden a la última actualización.

El cliente será responsable de la correcta utilización del tejido en lo que se refiere a las aplicaciones para las que está concebido y recomendado. S.A. Recasens declina toda responsabilidad en lo que se refiere al montaje y puesta en obra de sus productos. Así mismo declina toda responsabilidad en cuanto a la instalación de sus productos incumpliendo las normativas vigentes.

The indicated technical values are average values allowing a tolerance of +/- 5%.

Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. Recasens reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade.

The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. Recasens declines any responsibility in regard to the assembly and set in use on site of its products. Recasens declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place.

COLORES / COLORS

Bajo pedido / Upon request



R-004
Crema / Cream
RAL 1014



R-168
Verde Oscuro / Dark Green



R-094
Gris / Grey
RAL 7035