


Technical Textiles
PVC collection



STAR PLUS

TRANSPORTE Y GENERALES
TRANSPORT & GENERALS

RECASENS
BCN  1886

Technical Textiles
PVC collection

RECASENS
BCN  1886

We're woven differently

OFICINA CENTRAL / HEADQUARTERS:

Travessera de Gràcia, 18-20

08021 Barcelona (Spain)

Tel./Phone (+34) 93 200 27 00 · Fax (+34) 93 202 19 32

cial@recasens.com

export@recasens.com

www.recasens.com

[@recasensfabrics](https://www.instagram.com/recasensfabrics)





APLICACIONES / APPLICATIONS



CARACTERÍSTICAS DEL TEJIDO / FABRIC CHARACTERISTICS NORMA / NORM

Composición / Composition	Poliéster AT 1100 dtex recubierto de PVC / High Tenacity 1.100 dtex Polyester with PVC coating	
Tipo de tejido / Type of textile	Impermeable translúcido / Translucent waterproof finished	
Acabado / Finish	Liso brillante lacado a 1 cara / Glossy lacquered one side	
Uso / Use	Exterior / Outdoor	

CARACTERÍSTICAS TÉCNICAS / TECHNICAL FEATURES

Peso / Weight	610 g/m ²	UNE-EN ISO 2286-2
Espesor / Thickness	0,51 mm	UNE-EN ISO 2286-3
Ancho / Width	250 / 300 cm	
Longitud de pieza / Standard Roll Length	60 m	
Resistencia a la Tracción (Urdimbre / Trama) / Tensile Strength (Warp / Weft)	260/240 daN/5 cm	UNE-EN ISO 13934-1
Resistencia al Desgarro (Urdimbre / Trama) / Tear Strength (Warp / Weft)	50/30 daN	UNE-EN ISO 4674-1
Adherencia del recubrimiento / Coating adhesion	10 daN/5 cm	Método interno basado en Internal Method based on UNE-EN ISO 2411
Resistencia al frío y al calor / Heat and cold resistance	-30 °C / +70 °C	
Solidez del color a la luz artificial - Xenotest / Colour fastness to artificial light - Xenotest	7-8	UNE-EN ISO 105 B02
Solidez del color a la intemperie artificial - Xenotest / Colour fastness to artificial weathering - Xenotest	4-5	UNE-EN ISO 105 B04
Actividad antibacteriana / Antibacterial activity	Pasa / Pass	UNE-EN ISO 20645-05

Las características técnicas indicadas son valores medios con una tolerancia de +/- 5%.
Dado que nuestros productos están en constante evolución, en base a la demanda del mercado y a los avances técnicos, S.A. Recasens se reserva el derecho a modificar estos datos en todo momento, siendo responsabilidad del cliente verificar que los datos que está consultando corresponden a la última actualización.
El cliente será responsable de la correcta utilización del tejido en lo que se refiere a las aplicaciones para las que está concebido y recomendado. S.A. Recasens declina toda responsabilidad en lo que se refiere al montaje y puesta en obra de sus productos. Así mismo declina toda responsabilidad en cuanto a la instalación de sus productos incumpliendo las normativas vigentes.

*The indicated technical values are average values allowing a tolerance of +/- 5%.
Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. Recasens reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade.
The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. Recasens declines any responsibility in regard to the assembly and set in use on site of its products. Recasens declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place.*

COLORES / COLORS

R-099 Blanco / White RAL 9010 2,5 / 3 m	R-005 Marfil / Ivory RAL 1013 2,5 / 3 m	R-004 Crema / Cream RAL 1014 2,5 m	R-158 Beige RAL 1001 2,5 / 3 m	R-036 Amarillo / Yellow RAL 1018 2,5 m	R-555 Amarillo oscuro / Dark Yellow RAL 1003 2,5 m	R-567 Quisquilla / Orange RAL 2004 2,5 m	R-082 Rojo oscuro / Dark Red RAL 3002 2,5 m	R-075 Violeta / Violet RAL 4006 2,5 m	R-179 Granate / Burgundy RAL 3005 2,5 m
R-156 Marrón / Brown RAL 5010 2,5 m	R-174 Azul / Blue RAL 5015 2,5 / 3 m	R-073 Azul Europa / Blue RAL 5010 2,5 / 3 m	R-131 Pistacho / Pistachio 2,5 m	R-165 Manzana / Apple RAL 6024 2,5 m	R-166 Verde / Green RAL 6026 2,5 / 3 m	R-095 Gris claro / Light Grey RAL 7038 2,5m	R-096 Gris Oscuro / Dark Grey RAL 7037 2,5 m	R-092 Plata / Silver 2,5 m	R-090 Negro / Black RAL 9005 2,5 / 3 m