


Technical Textiles
PVC collection



NAUTIMAR

NÁUTICA
MARINE

RECASENS
BCN  1886

Technical Textiles
PVC collection

RECASENS
BCN  1886

We're woven differently

OFICINA CENTRAL / HEADQUARTERS:

Travessera de Gràcia, 18-20

08021 Barcelona (Spain)

Tel./Phone (+34) 93 200 27 00 · Fax (+34) 93 202 19 32

cial@recasens.com

export@recasens.com

www.recasens.com

[@recasensfabrics](https://www.instagram.com/recasensfabrics)





CARACTERÍSTICAS DEL TEJIDO / FABRIC CHARACTERISTICS NORMA / NORM

Composición / Composition	Poliéster AT 280 dtex. recubierto de PVC / High Tenacity 280 dtex. Polyester with PVC coating	
Tipo de tejido / Type of textile	Impermeable translúcido / Translucent waterproof finished	
Acabado / Finish	Recubierto, lacado y grabado en una cara / Coated, lacquered and embossed one side	
Uso / Use	Exterior / Outdoor	

CARACTERÍSTICAS TÉCNICAS / TECHNICAL FEATURES

Peso / Weight	330 g/m ²	UNE-EN ISO 2286-2
Espesor / Thickness	0,30 mm	UNE-EN ISO 2286-3
Ancho / Width	220 cm	
Longitud de pieza / Standard Roll Length	60 m	
Resistencia a la Tracción (Urdimbre / Trama) / Tensile Strength (Warp / Weft)	140/130 daN/5 cm	UNE-EN ISO 13934-1
Resistencia al Desgarro (Urdimbre / Trama) / Tear Strength (Warp / Weft)	11/11 daN	UNE-EN ISO 4674-1
Resistencia al frío y al calor / Heat and cold resistance	-30 °C / +70 °C	
Solidez del color a la luz artificial - Xenotest / Colour fastness to artificial light - Xenotest	7-8	UNE-EN ISO 105 B02
Solidez del color a la intemperie artificial - Xenotest / Colour fastness to artificial weathering - Xenotest	4-5	UNE-EN ISO 105 B04
Actividad antibacteriana / Antibacterial activity	Pasa / Pass	UNE-EN ISO 20645-05

Las características técnicas indicadas son valores medios con una tolerancia de +/- 5%.
Dado que nuestros productos están en constante evolución, en base a la demanda del mercado y a los avances técnicos, S.A. Recasens se reserva el derecho a modificar estos datos en todo momento, siendo responsabilidad del cliente verificar que los datos que está consultando corresponden a la última actualización.
El cliente será responsable de la correcta utilización del tejido en lo que se refiere a las aplicaciones para las que está concebido y recomendado. S.A. Recasens declina toda responsabilidad en lo que se refiere al montaje y puesta en obra de sus productos. Así mismo declina toda responsabilidad en cuanto a la instalación de sus productos incumpliendo las normativas vigentes.

*The indicated technical values are average values allowing a tolerance of +/- 5%.
Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. Recasens reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade.
The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. Recasens declines any responsibility in regard to the assembly and set in use on site of its products. Recasens declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place.*

COLORES / COLORS



R-097
Blanco nieve / Snow White


R-006
Cera / Off-White

R-525
Crema / Ivory

R-539
Arena / Sand

R-564
Gris Perla / Pearl Grey

R-563
Azul Royal / Royal Blue



R-195
Navy / Navy



R-090
Negro / Black

APLICACIONES / APPLICATIONS

