CRISTALREC 0,65

TECHNICAL DATA SHEET

100% PVC Transparent waterproof finished and reversible Smooth gloss finish 1 colour / Ref. 806 Indoor and Outdoor	
Smooth gloss finish 1 colour / Ref. 806	
1 colour / Ref. 806	
· · · · · · · · · · · · · · · · · · ·	
Indoor and Outdoor	
830 g/m ²	UNE-EN ISO 2286-2
0,65 mm	UNE-EN ISO 2286-3
137 cm	
30 m	
≤ 2,5% (23°C - 72 h)	Method T-206
≤ 4 kg/cm	Method T-210
Window cleaning fluid - No change Ammonia - No change Alcohol - Loss of shine and elasticity Bleach - No change Grease removing detergent - No change	UNE-EN ISO 2812-1
	ISO 9001
	0,65 mm 137 cm 30 m ≤ 2,5% (23°C - 72 h) ≤ 4 kg/cm Window cleaning fluid - No change Ammonia - No change Alcohol - Loss of shine and elasticity Bleach - No change

















The indicated technical values are average values allowing a tolerance of +/- 5%.

Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. RECASENS reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade. The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. RECASENS declines any responsibility in regard to the assembly and set in use on site of its products. S.A. RECASENS declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place.

