

| FABRIC CHARACTERISTICS | | NORM |
|--|---|--------------------|
| Composition | PVC coated polyester HT 280 dtex | |
| Type of fabric | Translucent waterproof finished | |
| Finish | Coated both sides and embossed one side | |
| Colour range | 2 colours | |
| Use | Outdoor | |
| TECHNICAL FEATURES | | |
| Weight | 460 g/m ² / 13.57 oz/yd ² | UNE-EN ISO 2286-2 |
| Thickness | 0,40 mm | UNE-EN ISO 2286-3 |
| Width | 220 cm / 86" | |
| Standard Roll Length | 60 m / 65 yards | |
| Tensile strength (warp/weft) | 140/130 daN/5 cm | UNE-EN ISO 13934-1 |
| Tear strength (warp/weft) | 6/7 daN | UNE-EN ISO 4674-1 |
| Resistance to cold and heat | -30 °C / +70 °C | |
| Resistance to chemical agents diluted in water | Window cleaning fluid - No change Ammonia - No change Alcohol - Loss of shine and elasticity Bleach - No change Grease removing detergent - No change | UNE-EN ISO 2812-1 |
| Antimicrobial activity | Formulated with products helping that bacteria and fungi do not adhere to the fabric | Statement |
| QUALITY MANAGEMENT SYSTEM | | |
| ISO 9001 | | ISO 9001 |
| SAFETY, HEALTH AND ENVIRONMENT | | |



RECASENS
BCN 1886



The indicated technical values are average values allowing a tolerance of +/- 5%.

Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. RECASENS reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade. The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. RECASENS declines any responsibility in regard to the assembly and set in use on site of its products. S.A. RECASENS declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place. Copyright © 2022 S.A. RECASENS. All rights reserved.

Technical Textiles
PVC collection