I e c c c c i l[®] Estampados

TECHNICAL DATA SHEET

NORM

FARDIC CHARACTERISTICS

FABRIC CHARACTERISTICS		NORM
Composition	70% Polyester fiber - 30% Solution-dyed acrylic fibre	
Type of fabric	Resin print	
Finish	Resin coated one side. Special "Infinity" treatment for awnings that repels water and dirt, creating an anti-stain and anti-mould barrier, whilst allowing the canvas to breathe	
Colour range	7 prints colours	
Use TECHNICAL FEATURES	Outdoor	
Weight	375 g/m ²	UNE-EN 12127
Thickness	0,56 mm	UNE-EN ISO 5084
Width	120 / 220 / 250 cm (depending on design)	
Standard roll length	60 m / 65.6 yards	
Water column	≥ 400 mm	UNE-EN 20811
Tensile strength (warp/weft)	270/140 daN/5 cm	UNE-EN ISO 13934-1
Tear strength (warp/weft)	7/4.5 daN	UNE-EN ISO 13937-2
Colour fastness to artificial light - Xenotest	4-5 (Good-Excellent) Grey scale 7-8 (Very good-Excellent) Blue scale	UNE-EN ISO 105 BO2
Colour fastness to artificial weathering - Xenotest	4 (Good) Grey scale	UNE-EN ISO 105 B04
Oil repellency	≥ 4	UNE-EN ISO 14419
Water repellency	≥ 4	UNE-EN ISO 4920
Resistance to chemical agents diluted in water	Window cleaning fluid - No change Ammonia - No change Alcohol - No change Bleach - No change Grease removing detergent - Slight darkening	UNE-EN ISO 2812-1
QUALITY MANAGEMENT SYSTEM		
ISO 9001		ISO 9001

SAFETY, HEALTH AND ENVIRONMENT



FTRECACRILESTAMPADOS/V1.4.2022



RECASENS BCN 🗖 1886



The indicated technical values are average values allowing a tolerance of +/- 5%.

Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. RECASENS reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade. The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. RECASENS declines any responsibility in regard to the assembly and set in use on site of its products. S.A. RECASENS declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place. Copyright © 2022 S.A. RECASENS. All rights reserved.