## **RECAFLEX LISTADO**

## **TECHNICAL DATA SHEET**

FABRIC CHARACTERISTICS		NORM
Composition	PVC coated polyester HT 1100 dtex	
Type of fabric	Reversible translucent waterproof	
Finish	Brilliant smooth lacquered on both sides	
Colour range	4 stripe colours	
	Outdoor	
TECHNICAL FEATURES		
Weight	700 g/m <sup>2</sup>	UNE-EN ISO 2286-2
[hickness	0,55 mm	UNE-EN ISO 2286-3
Width	220 cm	
Standard roll length	60 m / 65.6 yards	
Tensile strength (warp/weft)	295/300 daN/5 cm	UNE-EN ISO 13934-1
Elongation at break (warp/weft)	23.4/31.4%	
Tear strength (warp/weft)	50/30 daN	UNE-EN ISO 4674-1
Coating adhesion	10 daN/5 cm	Internal procedure based or UNE-EN ISO 2411
Resistance to cold and heat after tropicalisation test	-30°C / +70°C -22°F / +158°F	UNE 53243-22
Colour fastness to artificial light - Xenotest	4-5 (Good-Excellent) Grey scale 7-8 (Very good-Excellent) Blue scale	UNE-EN ISO 105 B02
Colour fastness to artificial weathering - Xenotest	4-5 (Good-Excellent) Grey scale	UNE-EN ISO 105 BO4
Performance in saline environment	No blistering. No cracking. No change	UNE-EN ISO 9227
Resistance to chemical agents diluted in water	Window cleaning fluid - No change Ammonia - No change Alcohol - Loss of shine and elasticity Bleach - No change Grease removing detergent - No change	UNE-EN ISO 2812-1
Antimicrobial activity	Pass	UNE-EN ISO 20645-05
Fire classification	M2	UNE-EN 23727
QUALITY MANAGEMENT SYSTEM		
ISO 9001 SAFETY, HEALTH AND ENVIRONMENT		ISO 9001
PHTHALAT	ES FREE LEAD FREE	NITE & CONTROL
Sistema de Gestión ISO 9001:2015 ISO 9001:2015 ISO 9001:2015 ISO 9001:2015	RECASENS BCN <b>n</b> 1886	VEARS VEARS

The indicated technical values are average values allowing a tolerance of +/- 5%.

The indicated technical values are average values allowing a tolerance of +/- 5%. Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. RECASENS reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade. The client is responsible for the correct use of the fabric in regard to the applications for which it is disgned and recommended. S.A. RECASENS declines any responsibility in regard to the assembly and set in use on site of its products. S.A. RECASENS declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place. Copyright © 2022 S.A. RECASENS. All rights reserved.

