

FABRIC CHARACTERISTICS		NORM
Composition	PVC coated polyester HT 1100 dtex	
Type of fabric	Reversible translucent waterproof	
Finish	Brilliant smooth lacquered both sides	
Colour range	11 colours	
Use	Outdoor	
TECHNICAL FEATURES		
Weight	700 g/m ²	UNE-EN ISO 2286-2
Thickness	0,59 mm	UNE-EN ISO 2286-3
Width	250 / 300 cm - 98" / 118"	
Standard Roll Length	60 m / 65 yards	
Tensile strength (warp/weft)	275/265 daN/5 cm	UNE-EN ISO 13934-1
Tear strength (warp/weft)	50/30 daN	UNE-EN ISO 4674-1
Coating adhesion	10 daN/5 cm	Internal procedure based on UNE-EN ISO 2411
Resistance to cold and heat	-30 °C / +70 °C	
Resistance to chemical agents diluted in water	Window cleaning fluid - No change Ammonia - No change Alcohol - Loss of shine and elasticity Bleach - No change Grease removing detergent - No change	UNE-EN ISO 2812-1
Antimicrobial activity	Formulated with products helping that bacteria and fungi do not adhere to the fabric	Statement
QUALITY MANAGEMENT SYSTEM		
ISO 9001		ISO 9001
SAFETY, HEALTH AND ENVIRONMENT		



RECASENS
BCN 1886



The indicated technical values are average values allowing a tolerance of +/- 5%.

Since our products are constantly adjusted to the market needs / technical advances and therefore in constant evolution, S.A. RECASENS reserves the right to modify this data at any time, and it is customer's responsibility to verify that data that being consulted or used corresponds to the latest upgrade. The client is responsible for the correct use of the fabric in regard to the applications for which it is designed and recommended. S.A. RECASENS declines any responsibility in regard to the assembly and set in use on site of its products. S.A. RECASENS declines all responsibility for the installation of its products if not used properly and / or in accordance with current regulations in place. Copyright © 2022 S.A. RECASENS. All rights reserved.

Technical Textiles
PVC collection